

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	TANK FLOOR	.5" MATERIAL	1
2	FLOOR TANK MOUNTS	ONE MOUNT PER EVERY 1000 GALLONS OF WATER	1
	STEEL PLATE	.5" MILD STEEL POWDER COATED	2
3	HAT CHANNEL BRACKET	.125" MILD STEEL POWDER COATED	1
4	1.5" X 1.5" CROSS MEMBER	.125" MILD STEEL(SUPPLIED BY CUSTOMER)	1
5	FLAT WASHER	.5" FLAT WASHER	6
6	.5-13 X 4.5" BOLT (91257A730) MCMASTER-CARR	APPLY LOCTITE TO BOLTS AND TORQUE TO 30 FOOT POUNDS	6
7	.25" RUBBER	SUPPLIED BY CUSTOMER	1
8	.5" RUBBER	SUPPLIED BY CUSTOMER	1
9	(9623K37) MCMASTER CARR	3" SPRING 9623K37	6

THESE DRAWINGS ARE THE EXCLUSIVE PROPERTY OF PRO POLY OF AMERICA ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE DISCLOSED IN WHOLE OR IN PART TO ANY OTHER PARTY AND THAT IT SHALL NOT BE COPIED IN ANY FORM WITHOUT THE PRIOR WRITTEN PERMISSION OF PRO POLY OF AMERICA

CUSTOMER ACCEPTANCE SIGNATURE REQUIRED			NOTE: TANK WILL NOT GO INTO PRODUCTION UNTIL CUSTOMER HAS SIGNED AND DATED FINAL DRAWING.			
CUSTOMER	SIGNATURE	DATE	PRO POLY® of America, Inc.	WATER CAPACITY	SCALE P.O. NUMBER 1:2	FINISH .
ENGINEERING BY	SIGNATURE	DATE	1821 N.W. 57TH STREET	FOAM CAPACITY	CUSTOMER TANK	TANK NO. FLOOR MOUNT
CHECKED BY	SIGNATURE	DATE	OCALA, FL 34475 PH.(352)629-1414 FAX(352)629-6049	TOTAL CAPACITY	MOUNT	FLOOR MOUNT
TOTAL TANK CAPICITY CERTIFICATION	SIGNATURE	DATE	ONELGG OTTIERWIGE OF ECITIED, DIWIENGIONG AIRE	DRAWN BY DATE CREATED C. SMITH 3/13/2009	ASSEMBLY	SASEMBLY REV. 2 OF 2 -